

## WST-630 Battery Powered Wireless Smoke Alarm

<b>Sensor type</b>	Thermoptek Multi-Sensor
<b>Battery type</b>	10 year sealed for life lithium




- Thermoptek Multi-Sensor technology as used by over 90% of the UK Fire and Rescue Services.
- 10 year sealed for life lithium battery.
- Large central button - Test / Smart Silence / locate.
- Smart Silence - allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound.
- Locate feature - when the network goes into alarm pressing the test button of any alarm will silence all but the initiating alarm.
- **Wi-Safe 2** technology - up to 50 **Wi-Safe 2** alarms can be interlinked on a single network.
- End of Life Indication - a clear reminder to replace the alarm, which can be silenced.
- Bug mesh and dust compensation - designed to reduce nuisance alarms and improve longevity.



2831  
EN 14604:2005+AC:2008  
Smoke Alarm Devices  
FSTDOP25014



## Technical Specification

<b>Dimensions</b>	132mm (diameter) x 40.5mm (depth)	
<b>Supply voltage</b>	3V DC	
<b>Battery</b>	10 year sealed for life battery	
<b>Sensor technology</b>	Thermoptek Multi-Sensor and Wi-safe 2	
<b>Alarm sound level</b>	85dB(A) at 3m (minimum)	
<b>Installation positions</b>	Ceiling / Wall	
<b>Operating temperature</b>	+4°C to +38°C	
<b>Operating humidity</b>	Up to 90% RH (non condensing)	
<b>Storage temperature</b>	-20°C to +60°C	
<b>Storage humidity</b>	Up to 93% RH (non condensing)	
<b>Warranty</b>	5 Years	
<b>Certified to</b>	BS EN 14604:2005 +AC:2008	
<b>Independently tested to</b>	EN 300 220-2 V2.4.1, EN 301 489-3 V1.6.1, EN 301 489-1 V1.9.2	
<b>Maximum number of connected units</b>	50 wireless units	
<b>Operating frequency</b>	868MHz	
<b>Range</b>	35m (over 200m in clear air)	
<b>Weight</b>	210g	
<b>Leisure Accomodation Vehicles</b>	Yes	